



# INSTALLATION INSTRUCTIONS

Product: Rear Adjustable Track Bar Rebuild Kit  
Part Number: JKS7205

Applications: JKSOGS155

877-533-7557 • jks@sporttruckusainc.com • www.jksmfg.com  
491 W. Garfield Avenue, Coldwater, MI 49036

## Welcome

CONGRATULATIONS on purchasing a Track Bar Rebuild Kit from JKS Manufacturing. We are committed to providing you with the best products available and your satisfaction is our first priority.

PLEASE READ these Installation Instructions carefully, and save them for future reference, as they contain important installation and maintenance information.

## Parts

Description	QTY
Urethane Bushing	4
Sleeve	2
Track Bar Decal	1

## Installation

### TRACK BAR REMOVAL

- Securely block wheels to prevent accidental movement of vehicle.
- Remove track bar from vehicle. Original installation instructions can be referenced if necessary.

### POLYURETHANE BUSHINGS

#### 1. REMOVAL

- Press out the sleeve from each end of the track bar.
- Using a screwdriver, pry out the two bushing halves from each end.
- Clean any corrosion or debris from the inner surface.

#### 2. INSTALLATION

- Liberally apply grease to the surface of the bushings.
- Press in two bushing halves into each end of the track bar with the lip toward the outside of the track bar.
- Apply grease to the sleeves and insert into each end of the track bar.

### FINAL STEPS

- Reinstall track bar. Reference original installation instructions if necessary.
- Verify jam nut is tight and did not move.
- If needed, a replacement decal is included.

## Maintenance

Check torque specifications regularly.

©2015 JKS Manufacturing  
Revision Date 03/11/2021